

## LOAD ARRESTOR: COMPACT


WLL	Max length	Connection type	Weight	Dimensions (L x l x h)	Braking distance	Max speed	Number of cycles (before replacement)	Wire rope Ø	Wire rope breaking force
250kg	10m	with connector	6kg	650 x 200 x 75 mm	750mm	35 m/min	10000	4.7mm (7 x 19 galva)	22 kN
250kg	15m	with connector	15kg	778 x 320 x 130 mm	750mm	35 m/min	10000	5mm (18 x 7 non-rotating)	22 kN
		with fixing bracket		805 x 320 x 130 mm					
500kg	10m	with connector	15kg	778 x 320 x 130 mm	750mm	35 m/min	10000	6.8mm (18 x 7 non-rotating)	37 kN

Load arrestor must be used in a vertical position

Anchor point must be calculated to support a vertical force of 20kN for 250kg and 30kN for 500kg

The Wharf,  
Bugbrooke,  
Northamptonshire,  
NN7 3QB, UK

Tel: +44 (0)1604 830083  
Fax: +44 (0)1604 831144  
Email: [info@unusual.co.uk](mailto:info@unusual.co.uk)  
Web: [www.unusual.co.uk](http://www.unusual.co.uk)



**UNUSUAL**