

## LINEAR WINCH Compact


Speed (m/s)	0.8	1.2
Load (kg)	300	
Engine		
Type	asynchronous	
Power (kW)	4	5.5
Voltage (V)	230/400 V 50Hz	
Reducer		
Type	Helical bevel gear reducer	
Outgoing Torque (Nm)	379	379
Brake		
Torque (Nm)	2 x 50	2 x 75
Type TR2-SIL3	BGV-D8+ / BGV-C1 /SIL3 – theatre version – double silent pressure brake. Activates on power out.	
Limit Switch		
Type	Cam switch on axle at drive end	
Number of contacts	4 x NC of 8 x NC – dependent on application	
Steel cables		
Type	19 x 7 – with steel core – certified	
Drum		
Diameter	164	
Cable attachment	1 x clamp plate per wire – 3 safety windings	

### OPTIONS

- Incremental encoder for speed regulation
- Absolute encoder for position determination
- Monitoring of the engine temperature
- Slack cable detection
- Overload detection

The Wharf,  
Bugbrooke,  
Northamptonshire,  
NN7 3QB, UK

Tel: +44 (0)1604 830083  
Fax: +44 (0)1604 831144  
Email: [info@unusual.co.uk](mailto:info@unusual.co.uk)  
Web: [www.unusual.co.uk](http://www.unusual.co.uk)



**UNUSUAL**

